

View Online at <https://aerobasegroup.com/nsn/5305-00-984-7341>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.563 inches and 0.625 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.340 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: ch47 chinook unique avionics-qw; communications terminal, satellite an/gsc-3 (v)1; support equipment, b-1 aircraft; engine, aircraft f110-ge-400; aviation engine test systems (aets); deep submergence systems programs (dssp); helicopter, mh-53e; aircraft, c-2a (reprocured) ; fire pumps; torpedo, mk 48

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1013

**Screw Material Specification:**

66 federal standard all material responses

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0