## NSN 5305-00-985-0816

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-985-0816 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.180 inches **Fastener Length:** Between 1.310 inches and 1.330 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.076 inches and 0.084 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.130 inches and 1.150 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point Material: Stainless steel **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-985-0816

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.