## NSN 5305-00-986-9997

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-986-9997 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.437 inches **Fastener Length:** 2.954 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.312 inches **Head Height:** 0.109 inches First Diameter From Head: 0.190 inches **Second Diameter From Head:** 0.120 inches **Third Diameter From Head:** 0.190 inches **Fourth Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.000 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.736 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.798 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.517 inches **Internal Drive Style: Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 

4

Material:

Steel comp 302 or steel comp 303 or steel comp 304

**Material Specification:** 

Qq-s-763, cond a federal specification 1st material response or astm a582 cond a assn standard 2nd material response or qq-s-763, cond a federal specification 3rd material response

## NSN 5305-00-986-9997

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0