

View Online at <https://aerobasegroup.com/nsn/5305-00-986-9997>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.437 inches

**Fastener Length:**

2.954 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

0.312 inches

**Head Height:**

0.109 inches

**First Diameter From Head:**

0.190 inches

**Second Diameter From Head:**

0.120 inches

**Third Diameter From Head:**

0.190 inches

**Fourth Diameter From Head:**

0.120 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

1.000 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.736 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.798 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

2.517 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304

**Material Specification:**

Qq-s-763, cond a federal specification 1st material response or astm a582 cond a assn standard 2nd material response or qq-s-763, cond a federal specification 3rd material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0