

View Online at <https://aerobasegroup.com/nsn/5305-00-987-0062>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.251 inches and 0.311 inches

Fastener Length:

Between 0.770 inches and 0.790 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.200 inches and 0.240 inches

Head Height:

Between 0.170 inches and 0.190 inches

Shoulder Diameter:

0.290 inches first shoulder and 0.310 inches first shoulder

Shoulder Length:

0.400 inches first shoulder and 0.420 inches first shoulder

Shank Unthreaded Hole Diameter:

0.046 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.050 inches and 0.150 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.670 inches first hole and 0.690 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Thd relieved groove 0.100 in. Min 0.190 in. Maximum diameter by 0.089 in. Nom w

Material:

Stainless steel

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0