Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-0991

| Thread Cla | ISS: |
|-------------|--|
| 2a | |
| Thread Dir | ection: |
| Right-hand | |
| Thread Le | ngth: |
| 0.390 inche | IS |
| Fastener L | ength: |
| 1.000 inche | IS |
| Head Style | c |
| Hexagon | |
| Head Heig | ht: |
| 0.156 inche | S |
| Width Bety | veen Flats: |
| 0.437 inche | S |
| First Diam | eter From Head: |
| 0.250 inche | S |
| Second Di | ameter From Head: |
| Between 0. | 118 inches and 0.123 inches |
| Distance F | rom Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.531 inche | S |
| Distance F | rom Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.610 inche | S |
| Internal Dr | ive Style: |
| Cross rece | ss type 1 |
| Thread Dia | imeter: |
| 0.164 inche | S |
| Thready Q | ty Per Inch (tpi): |
| 32 | |
| Externally | Relieved Body Diameter Quantity: |
| 2 | |
| Material: | |
| Steel comp | 303 |
| Material S | pecification: |
| Mil-s-7720 | military specification single material response |
| Surface Tr | eatment: |
| Passivate | |
| Thread Se | ries Designator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Me | asure: |

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.