NSN 5305-00-988-1482

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-1482 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.231 inches **Fastener Length:** 0.312 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** Between 0.213 inches and 0.223 inches **Secondary Washer Outside Diameter:** 0.212 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.013 inches and 0.019 inches **Secondary Washer Material Thickness:** 0.025 inches Material: Steel comp 1010 **Material Specification:** Qq-s-634 federal specification single material response

Surface Treatment:

Cadmium and chromate

NSN 5305-00-988-1482

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Specification Data:
80205-nas720 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0