NSN 5305-00-988-6110

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-6110 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.338 inches **Fastener Length:** Between 0.823 inches and 0.853 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.337 inches and 0.385 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches grin ırd

33.0 microinches grip
Material:
Titanium alloy uns r54520
Material Specification:
Nas 621, 6al-4v assn standard single material response
Thread Series Designator:
Jnf
Specification Data:
30205-nas663 professional/industrial association standa
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

NSN 5305-00-988-6110

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0