## NSN 5305-00-988-6763

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-6763 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.294 inches **Fastener Length:** 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.212 inches **Secondary Washer Outside Diameter:** 0.218 inches **Primary Washer Style:** Split helical ring **Secondary Washer Material Thickness:** 0.015 inches Material: Steel comp 1010 **Material Specification:** Qq-s-633 federal specification single material response **Surface Treatment:** Cadmium

**Thread Series Designator:** 

Unc

## NSN 5305-00-988-6763

Assembled Washer Screw - Page 2 of 2



S	pec	ific	cati	on	Data:

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0