

View Online at <https://aerobasegroup.com/nsn/5305-00-988-7610>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.762 inches and 0.875 inches

**Fastener Length:**

Between 0.845 inches and 0.875 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Mrap rg-33; mrap rg-33 auv

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.158 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Stainless steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

6 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0