Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-7794

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.666 inches
Fastener Length:
0.750 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.480 inches and 0.531 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
0.156 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
30000 pounds per square inch
Countersink Angle:
Between 80.0 degrees and 84.0 degrees
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

steel comp 316

NSN 5305-00-988-7794

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

