## NSN 5305-00-988-7847

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-988-7847 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** Between 2.210 inches and 2.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.563 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.313 inches and 0.316 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch **Special Features:** Grip length 1.000 in. Max; body length 0.687 in. Min; head chamfer 30.0 degrees min 45.0 degrees max; head may be knurled at mfr option Color: Natural Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** 

Unc

**Specification Or Standard:** 

**Thread Series Designator:** 

Qq-p-35 federal specification single treatment response

6 type

## NSN 5305-00-988-7847

Socket Head Cap Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0