## NSN 5305-00-990-9224

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-990-9224 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.328 inches and 0.469 inches **Fastener Length:** Between 0.454 inches and 0.501 inches **Head Style:** Round **Head Diameter:** Between 0.361 inches and 0.385 inches **Head Height:** Between 0.103 inches and 0.118 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 248.0 brinell standard and 321.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0

## NSN 5305-00-990-9224

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.