NSN 5305-00-991-3187

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-991-3187 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.765 inches and 0.797 inches **Fastener Length:** Between 0.968 inches and 1.015 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.985 inches and 1.016 inches **Head Height:** Between 0.235 inches and 0.266 inches **Shoulder Diameter:** 0.515 inches first shoulder and 0.531 inches first shoulder **Shoulder Length:** 0.187 inches first shoulder and 0.234 inches first shoulder **Point Style: Pointless Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 or steel comp 304 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A003b0

NSN 5305-00-991-3187

Thumbscrew - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.