NSN 5305-00-991-3412

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-991-3412 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 1.250 inches **Head Style:** Fillister **Head Diameter:** 0.406 inches **Head Height:** 0.153 inches **First Diameter From Head:** 0.234 inches **Second Diameter From Head:** Between 0.170 inches and 0.172 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.050 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.781 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** E300 fscm 13499 mfr ref single treatment response **Thread Series Designator:** Unc

٠.

Shelf Life:

N/a

NSN 5305-00-991-3412

Externally Relieved Body Screw - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0