NSN 5305-00-991-5865

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-991-5865 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.111 inches and 0.132 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.282 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Furnished w/one rectangular washer and one no. 6 split lock washer Material: Steel comp 303 **Material Specification:** Qq-s-763, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-991-5865

Externally Relieved Body Screw - Page 2 of 2



			on:	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.