NSN 5305-00-991-6520



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-991-6520 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.362 inches **Fastener Length:** Between 1.050 inches and 1.090 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.491 inches and 0.507 inches **Shoulder Diameter:** 0.246 inches first shoulder and 0.249 inches first shoulder **Shoulder Length:** 0.592 inches first shoulder and 0.612 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1299 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-991-6520

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0