Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-992-5851

Thread	Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.750 inches

Fastener Length:

0.750 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

35.0 rockwell c and 36.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 304

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Test Data Document:

81348-ffs86 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Or 96906-ms16995-20 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unc

Specification Or Standard:

modified by motorial

6 type

Departure From Cited Document:

NSN 5305-00-992-5851

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator:

As modified by condition a

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0