Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-992-5915



# Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.908 inches and 1.000 inches

## Fastener Length:

Between 0.970 inches and 1.000 inches

## Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

## Head Height:

Between 0.159 inches and 0.164 inches

## Internal Drive Style:

Hexagon

## Thread Diameter:

0.164 inches

## Width Across Flats:

Between 0.141 inches and 0.143 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

80000 pounds per square inch

#### Minimum Yield Strength:

30000 pounds per square inch

#### Material:

Steel comp 304

## Material Specification:

Qq-s-763 federal specification single material response

## Surface Treatment:

Passivate

## Test Data Document:

81348-ffs86 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Or 96906-ms16995-30 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unc

## Specification Or Standard:

6 type

Departure From Cited Document:

As modified by material

Departure From Cited Designator:

modified by condition a

# NSN 5305-00-992-5915

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

