

View Online at <https://aerobasegroup.com/nsn/5305-00-992-5942>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.625 inches

**Fastener Length:**

0.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.313 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.159 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

35.0 rockwell c and 36.0 rockwell c

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 304

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Test Data Document:**

81348-ffs86 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-ms16996-11 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Thread Series Designator:**

Unf

**Specification Or Standard:**

6 type

**Departure From Cited Document:**

As modified by material

**Departure From Cited Designator:**

As modified by condition a

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0