NSN 5305-00-992-6138

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-992-6138

view Offilite at https://defobasegroup.com/hsr//5505-50-552-5150
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.313 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 304
Material Specification:
Qq-s-763 cond a federal specification single material response
Surface Treatment:
Passivate
Test Data Document:
81348-ffs86 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmenta
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-ms16695-62 standard
(includes industry or association standards, individual manufactureer standards, etc.).
Thread Series Designator:
Unc

As modified by meterial

6 type

Specification Or Standard:

Departure From Cited Document:

NSN 5305-00-992-6138

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0