## NSN 5305-00-992-7331

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-992-7331 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.560 inches **Fastener Length:** 1.210 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.750 inches **Head Height:** 0.250 inches **First Diameter From Head:** 0.440 inches **Second Diameter From Head:** 0.192 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.120 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.650 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

## NSN 5305-00-992-7331

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:
•	•	uuuu.u.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.