NSN 5305-00-993-7199

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-993-7199

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.829 inches
Fastener Length:
0.875 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate

Passivate

NSN 5305-00-993-7199

Socket Head Cap Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0