NSN 5305-00-993-8848

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-993-8848 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.185 inches and 0.215 inches **Fastener Length:** Between 0.235 inches and 0.265 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Stainless steel **Material Specification:** 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-s-35 federal specification single treatment response **Thread Series Designator:**

Unc Shelf Life:

N/a

NSN 5305-00-993-8848

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0