

View Online at <https://aerobasegroup.com/nsn/5305-00-995-0575>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.250 inches

**Fastener Length:**

1.250 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.359 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

82.0 degrees

**Screw Material:**

Steel comp 304

**Screw Material Specification:**

Qq-s-763 federal specification single material response

**Screw Surface Treatment:**

Passivate

**Test Data Document:**

81348-ffs92 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-ms51960-75 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Thread Series Designator:**

Unf

**Specification Or Standard:**

3 type and 2c style

**Departure From Cited Document:**

As modified by material

**Departure From Cited Designator:**

As modified by condition a

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A500d0