

View Online at <https://aerobasegroup.com/nsn/5305-00-995-0629>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

2.000 inches

**Fastener Length:**

2.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.600 inches and 0.635 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

82.0 degrees

**Screw Material:**

Steel comp 304

**Screw Material Specification:**

Qq-s-763 federal specification single material response

**Screw Surface Treatment:**

Passivate

**Test Data Document:**

81348-ffs92 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-51959-1021 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type and 2c style

**Departure From Cited Document:**

As modified by material

**Departure From Cited Designator:**

As modified by condition a

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A500d0