

View Online at <https://aerobasegroup.com/nsn/5305-00-995-2117>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.500 inches and 0.562 inches

**Fastener Length:**

0.562 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.105 inches and 0.115 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Screw Material:**

Steel comp 8630

**Screw Material Specification:**

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.