

View Online at <https://aerobasegroup.com/nsn/5305-00-999-4586>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.219 inches and 0.312 inches

Fastener Length:

Between 0.281 inches and 0.312 inches

Head Style:

Fillister

Head Diameter:

Between 0.250 inches and 0.270 inches

Head Height:

Between 0.106 inches and 0.113 inches

Locking Feature:

Pellet threads

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0