## NSN 5305-00-999-5314



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-999-5314 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 2.094 inches and 2.156 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.160 inches and 0.164 inches **Hole Diameter:** Between 0.043 inches and 0.051 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.141 inches and 0.143 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 125000 pounds per square inch **Hole Configuration Style:** Hexagon longitudinal hole Material: Iron alloy 660

**Material Specification:** 

Ams 5731 assn standard single material response or ams 5734 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-00-999-5314

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0