NSN 5305-01-004-1967

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-004-1967 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.620 inches **Fastener Length:** 6.200 inches **Head Style:** Flat chamfer **Head Diameter:** 0.500 inches **Head Height:** 0.375 inches **First Diameter From Head:** Between 0.184 inches and 0.192 inches **Second Diameter From Head:** Between 0.147 inches and 0.149 inches **Third Diameter From Head:** Between 0.184 inches and 0.192 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.320 inches and 0.340 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.352 inches and 0.369 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 5.211 inches and 5.235 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Knurled head Material: Steel comp 316 **Material Specification:**

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

NSN 5305-01-004-1967

Externally Relieved Body Screw - Page 2 of 2



Qq-p-35, type 1 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0