NSN 5305-01-004-1971

2a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-004-1971

Thread Class:

Thread Direction:
Right-hand
Thread Length:
0.240 inches
Fastener Length:
0.420 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.155 inches and 0.167 inches
Head Height:
Between 0.045 inches and 0.053 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Grip Diameter:
Between 0.0860 inches and 0.0870 inches
Internal Drive Style:
Slot
Thread Diameter:
0.086 inches
Grip Length:
- I
0.180 inches
0.180 inches
0.180 inches Thready Qty Per Inch (tpi):
0.180 inches Thready Qty Per Inch (tpi): 56
0.180 inches Thready Qty Per Inch (tpi): 56 Material:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response Thread Series Designator:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response Thread Series Designator: Unc
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response Thread Series Designator: Unc Shelf Life:
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a
0.180 inches Thready Qty Per Inch (tpi): 56 Material: Steel comp 304 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Surface Treatment Specification: Ns177, fscm 12511 mfr ref single treatment response Thread Series Designator: Unc Shelf Life: N/a

NSN 5305-01-004-1971

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0