NSN 5305-01-004-4044

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-004-4044 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.265 inches **Fastener Length:** Between 0.583 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.076 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.345 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/alr-56c **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 2nd material response or comp 16-8 or 18-8 assn standard 3rd material response **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Mil-f-14072 military specification 1st treatment response and mil-c-13924 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-004-4044

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.