## NSN 5305-01-004-4094

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-004-4094 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.351 inches and 0.402 inches **Fastener Length:** Between 3.226 inches and 3.246 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.722 inches and 0.740 inches **Head Height:** Between 0.189 inches and 0.204 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.3737 inches and 0.3742 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.688 inches and 2.704 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.099 inches first hole and 3.119 inches first hole **Surface Finish:** 32.0 microinches grip

Material: Steel comp 630 **Material Specification:** Ams 5643 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 1 federal specification single treatment response **Thread Series Designator:** Unjf

## NSN 5305-01-004-4094

Close Tolerance Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0