

View Online at <https://aerobasegroup.com/nsn/5305-01-004-9480>

**Fastener Length:**

Between 1.204 inches and 1.250 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.340 inches and 0.385 inches

**Internal Drive Style:**

Slot

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Nonmachine Thread Style:**

Gimlet point (type a, ab or ba)

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Nonmachine Thread Diameter:**

0.190 inches

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316

**Material Specification:**

Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Specification Or Standard:**

1 type and 2s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0