

View Online at <https://aerobasegroup.com/nsn/5305-01-004-9480>

Fastener Length:

Between 1.204 inches and 1.250 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Internal Drive Style:

Slot

Min. Tensile Strength (psi):

70000 pounds per square inch

Nonmachine Thread Style:

Gimlet point (type a, ab or ba)

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Nonmachine Thread Diameter:

0.190 inches

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316

Material Specification:

Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Or Standard:

1 type and 2s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0