NSN 5305-01-005-4022

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-005-4022

Thread Class:							
3a							
Thread Direction:							
Right-hand							
Thread Length:							
Between 0.381 inches and 0.448 inches							
Fastener Length:							
Between 0.703 inches and 0.750 inches							
Head Style:							
Flat countersunk undercut							
Head Diameter:							
Between 0.377 inches and 0.381 inches							
Head Height:							
Between 0.044 inches and 0.046 inches							
Grip Diameter:							
Between 0.1890 inches and 0.1895 inches							
Internal Drive Style:							
High-torque							
Thread Diameter:							
0.190 inches							
Grip Length:							
Between 0.302 inches and 0.322 inches							
Thready Qty Per Inch (tpi):							
32							
Min. Tensile Strength (psi):							
125000 pounds per square inch							
Countersink Angle:							
Between 99.0 degrees and 101.0 degrees							
Surface Finish:							
32.0 microinches threads							
Special Features:							
Furnished w/one o-ring							
Material:							
Steel comp xm-13							
Material Specification:							
Ams 5629 assn standard single material response							
Surface Treatment:							
Passivate							
Thread Series Designator:							
Unjf							
Shelf Life:							

N/a

NSN 5305-01-005-4022

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0