

View Online at <https://aerobasegroup.com/nsn/5305-01-005-8631>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.115 inches and 0.135 inches

**Fastener Length:**

Between 0.812 inches and 0.822 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**First Diameter From Head:**

Between 0.096 inches and 0.099 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.687 inches and 0.697 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

An/alq-13 (v)

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 410

**Material Specification:**

Qq-s-763, cond h federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0