## NSN 5305-01-006-0296

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-006-0296 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.637 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.312 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.2500 inches and 0.2530 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

## NSN 5305-01-006-0296

Socket Head Cap Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0