## NSN 5305-01-006-2076

Shoulder Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.505 inches and 0.572 inches Fastener Length: Between 2.015 inches and 2.062 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.628 inches and 0.633 inches **Shoulder Diameter:** 0.326 inches first shoulder and 0.327 inches first shoulder Shoulder Length: 1.406 inches first shoulder and 1.428 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 100.0 degrees Shoulder Shape: Round first shoulder **Product Name:** Navy special project **Special Features:** Shank grooved near head to accommodate o ring, furnished with one o ring Material: Steel **Material Specification:** 3-53 fscm 76301 mfr ref single material response Surface Treatment: Cadmium **Surface Treatment Specification:** 3-53 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

## NSN 5305-01-006-2076

Shoulder Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

