NSN 5305-01-006-2405

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-006-2405 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.307 inches and 0.317 inches **Fastener Length:** Between 0.656 inches and 0.661 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.302 inches and 0.322 inches **Head Height:** Between 0.146 inches and 0.166 inches **Shoulder Diameter:** 0.185 inches first shoulder and 0.186 inches first shoulder **Shoulder Length:** 0.250 inches first shoulder and 0.255 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-006-2405

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.