## NSN 5305-01-006-5008

Close Tolerance Screw - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5305-01-006-5008

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.419 inches
Fastener Length:
1.219 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.502 inches and 0.507 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
28
28
28 Min. Tensile Strength (psi):
28 <b>Min. Tensile Strength (psi):</b> 160000 pounds per square inch
28 <b>Min. Tensile Strength (psi):</b> 160000 pounds per square inch <b>Countersink Angle:</b>
28 <b>Min. Tensile Strength (psi):</b> 160000 pounds per square inch <b>Countersink Angle:</b> 100.0 degrees
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish:
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material:
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 Material Specification:
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response
<ul> <li>28</li> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Countersink Angle:</li> <li>100.0 degrees</li> <li>Surface Finish:</li> <li>32.0 microinches threads</li> <li>Material:</li> <li>Steel comp 4130</li> <li>Material Specification:</li> <li>Mil-s-6758 military specification single material response</li> <li>Surface Treatment:</li> </ul>
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Primer bearing surface of head
<ul> <li>28</li> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Countersink Angle:</li> <li>100.0 degrees</li> <li>Surface Finish:</li> <li>32.0 microinches threads</li> <li>Material:</li> <li>Steel comp 4130</li> <li>Material Specification:</li> <li>Mil-s-6758 military specification single material response</li> <li>Surface Treatment:</li> <li>Primer bearing surface of head</li> <li>Surface Treatment Specification:</li> </ul>
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Primer bearing surface of head Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Primer bearing surface of head Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator:
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Material: 32.0 microinches threads Material: Steel comp 4130 Material Specification: Mil-s-6758 military specification single material response Surface Treatment: Primer bearing surface of head Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator: Unjf

## NSN 5305-01-006-5008

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.