

View Online at <https://aerobasegroup.com/nsn/5305-01-006-7188>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.125 inches

**Fastener Length:**

1.125 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.322 inches

**Locking Feature:**

Strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, clb federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1189 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.