# NSN 5305-01-006-8854

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-006-8854

Thread	Class:

2a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.200 inches

#### Fastener Length:

Between 0.340 inches and 0.370 inches

#### **Head Style:**

Flat chamfer

Head Diameter:

Between 0.256 inches and 0.261 inches

### **Head Height:**

Between 0.095 inches and 0.105 inches

Internal Drive Style:

Hexagon

### Material Accommodated Thickness:

Between 0.050 inches and 0.060 inches

## **Thread Diameter:**

0.138 inches

## Width Across Flats:

Between 0.1094 inches and 0.1111 inches

## Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

Color:

Black

### Material:

Steel comp 304 stand-off

### **Material Specification:**

II-s-23195 military specification single material response stand-off

#### **Surface Treatment:**

Oxide

### Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response or mil-c-13924 cl 3 military specification single treatment response

### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5305-01-006-8854

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.