NSN 5305-01-006-8855

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-006-8855 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.420 inches and 0.450 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.256 inches and 0.261 inches **Head Height:** Between 0.095 inches and 0.105 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.050 inches and 0.060 inches **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Color: Black Material: Steel comp 302 springsteel comp 304 stand-offiron alloy 660 fastener **Material Specification:** Astm a580 cond b assn standard single material response springmil-s-23195 military specification single material response stand-offams 5737 assn standard single material response fastener **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response or mil-c-13924 cl 3 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-006-8855

Panel Screw Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-23195 spec.