## NSN 5305-01-006-8942

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-006-8942 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.366 inches and 0.412 inches **Fastener Length:** Between 1.266 inches and 1.312 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **First Diameter From Head:** Between 0.145 inches and 0.155 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.900 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-006-8942

Externally Relieved Body Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.