

View Online at <https://aerobasegroup.com/nsn/5305-01-007-0474>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.320 inches

**Fastener Length:**

1.070 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.311 inches and 0.312 inches

**Head Height:**

Between 0.095 inches and 0.105 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.077 inches first hole and 0.082 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.750 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.960 inches first hole

**Material:**

Steel comp 324

**Material Specification:**

Mil-s-862 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

E+1204 fscm 28652 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-862 spec.