

View Online at <https://aerobasegroup.com/nsn/5305-01-007-1493>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.136 inches and 0.229 inches

Fastener Length:

Between 0.281 inches and 0.312 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.333 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

55000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 764 or copper alloy 770

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 3c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.