## NSN 5305-01-007-1537

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-007-1537 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.386 inches and 0.453 inches **Fastener Length:** Between 0.708 inches and 0.755 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** 0.312 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification single treatment response or nas672 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5305-01-007-1537

Close Tolerance Screw - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.