NSN 5305-01-007-4660

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-007-4660 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.280 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.094 inches and 0.107 inches **Hole Diameter:** 0.037 inches First Diameter From Head: Between 0.079 inches and 0.084 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.345 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 40 Minimum Yield Strength: 80000 pounds per square inch **Hole Configuration Style:** Round **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses

Surface Treatment:

Passivate

NSN 5305-01-007-4660

Externally Relieved Body Screw - Page 2 of 2



Surface	Treatment	Specifi	cation:
Juliace	I I Callillelli	Speciii	calion.

Qq-p-35, type 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0