NSN 5305-01-007-4874

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-007-4874

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.251 inches and 0.301 inches |
| Fastener Length: |
| Between 2.511 inches and 2.541 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.306 inches and 0.322 inches |
| Head Height: |
| Between 0.105 inches and 0.115 inches |
| Grip Diameter: |
| Between 0.1625 inches and 0.1635 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Grip Length: |
| Between 2.240 inches and 2.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Navy special project |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Nas621, comp 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-007-4874

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

